## Features:

1. Material: Anodized Aluminum 6063 + PC
2. Max. Single Profile length: 8ft 2in (2.5m)
3. Max. Run Length: 12ft (powered by class 2 driver)
4. Operating Temperature: -20°C~45°C
5. Environment: Dry indoor locations only
6. Lifespan: 50,000 hours
7. Certification: ⓤ US LISTED
8. Warranty: 5 years
9. Dimming: Dimmable (see driver options)

Dimensions: 1 15/16" [49mm], 1 3/16" [30mm], [38mm], 1 1/4" [32mm], 2 1/2" [63mm]

Working Voltage (V)	DC24V
Input power (W/ft)	9.1
Beam Angle (°)	105.6

CCT	Source Brightness lm/ft	Delivery Brightness lm/ft	Source Efficiency lm/W	Delivery Efficiency lm/W
2700K	1063	709	117	78
3000K	1169	780	128	86
4000K	1229	820	135	90

*Tested Samples: 4FT Aluminum with JLS8280-30mm LED strip

| Model	Finish	Length*	CCT	Installation
LE6332	WH: White BK: Black	4ft 8ft Customized	27: 2700K 30: 3000K 40: 4000K	A: Recessed

Project:

Qty:

Date:

Client:

Notes:

Installation:

A Recessed installation with remote driver (in juction box).

*Length definition

Length
Profile root length with 2 end caps
flange not included

Flange width on end cap : 7 mm