

<b>JLS3120</b>	<b>24</b>	<b>8</b>	<b>AA</b>	<b>BB</b>	<b>80</b>	<b>DD</b>
----------------	-----------	----------	-----------	-----------	-----------	-----------


Model	Voltage	Width	CCT	IP	CRI	Length
	24: 24V	8: 8mm	27: 2700K 30: 3000K 40: 4000K 60: 6000K	33: IP33 (Dry) 55: IP55 (Wet) 65: IP65 (Wet) 67: IP67 (Wet)	80: 80+	5m (SD) 50m (MS) Customized



CCT	Power	Brightness	Luminous Flux
2700K	2.93 W/ft	243 lm/ft	83 lm/W
3000K	2.93 W/ft	255 lm/ft	87 lm/W
4000K	2.93 W/ft	267 lm/ft	91 lm/W
6000K	2.93 W/ft	252 lm/ft	86 lm/W

<b>Project</b>	
<b>Qty</b>	
<b>Date</b>	
<b>Client</b>	

**Standard CCT**



<b>LED Type</b>	SMD3528 white
<b>Input Voltage</b>	24VDC
<b>Beam Angle</b>	120°
<b>CRI</b>	80+
<b>Power</b>	9.6W/M (2.93W/ft.)
<b>Current</b>	0.4A/m (0.12A/ft)
<b>Brightness</b>	243lm/ft (2700K); 255lm/ft(3000K); 267lm/ft (4000K); 252lm/ft (6000K)
<b>Length/ Reel</b>	5m(16.4ft)/ 50m/(164ft)
<b>Cut Length</b>	50mm/unit (1.97in/unit)
<b>Max. Length</b>	7m
<b>IP Grade</b>	IP33/ IP55/ IP65/ IP67
<b>Operating Temperature</b>	-20°C~45°C
<b>Environment Humidity</b>	40-70% RH
<b>LED CCT</b>	3000K/ 4000K
<b>Dimming Method</b>	0-10V, RX, PWM, Triac, RF, Bluetooth, WIFI etc.
<b>Certification</b>	CE, UL, RoHS

**Waterproof Solution**

<b>IP33</b> No waterproof Dry location	<b>IP55</b> Silicone Coating Wet location
<b>IP65</b> Waterproof Wet location	<b>IP67</b> Silicone Extrusion Wet location Short time under water

**DIMENSION**

