

JLS360	24	8	AA	BB	80	DD
--------	----	---	----	----	----	----


Model	Voltage	Width	CCT	IP	CRI	Length
	24: 24V	8: 8mm	30: 3000K 40: 4000K	33: IP33 (Dry) 55: IP55 (Wet) 65: IP65 (Wet) 67: IP67 (Wet)	80: 80+	5m (SD) 50m (MS) Customized



CCT	Power	Brightness	Luminous Flux
3000K	1.46 W/ft	128 lm/ft	88 lm/W
4000K	1.46 W/ft	134 lm/ft	92 lm/W

Project	
Qty	
Date	
Client	

## Standard CCT



## Waterproof Solution

<b>IP33</b> No waterproof Dry location	<b>IP55</b> Silicone Coating Wet location
<b>IP65</b> Waterproof Wet location	<b>IP67</b> Silicone Extrusion Wet location Short time under water

<b>LED Type</b>	SMD3528 white
<b>Input Voltage</b>	24VDC
<b>Beam Angle</b>	120°
<b>CRI</b>	80+
<b>Power</b>	4.8W/M (1.46W/ft.)
<b>Current</b>	0.2A/m (0.06A/ft)
<b>Brightness</b>	128lm/ft (3000K); 134lm/ft(4000K)
<b>Length/ Reel</b>	5m(16.4ft)/ 50m(164ft)
<b>Cut Length</b>	100mm/unit (3.94in/unit)
<b>Max. Length</b>	7m
<b>IP Grade</b>	IP33/ IP55/ IP65/ IP67
<b>Operating Temperature</b>	-20°C~45°C
<b>Environment Humidity</b>	40-70% RH
<b>LED CCT</b>	3000K/ 4000K
<b>Dimming Method</b>	0-10V, RX, PWM, Triac, RF, Bluetooth, WIFI etc.
<b>Certification</b>	CE, UL, RoHS

## DIMENSION

