

JLS560RGBW	24	12	AA	BB	80	DD
------------	----	----	----	----	----	----

Model	Voltage	Width	CCT	IP	CRI	Length
	24: 24V	12: 12mm	30: 3000K 40: 4000K	33: IP33 (Dry) 55: IP55 (Wet) 65: IP65 (Wet) 67: IP67 (Wet)	80: 80+	5m (SD) 50m (MS) Customized




CCT	Power	Brightness	Luminous Flux
RGBW	5.85 W/ft	270 lm/ft	46 lm/W
R	1.46 W/ft	35 lm/ft	24 lm/W
G	1.46 W/ft	91 lm/ft	62 lm/W
B	1.46 W/ft	27 lm/ft	18 lm/W
3000K	1.46 W/ft	113 lm/ft	77 lm/W
4000K	1.46 W/ft	116 lm/ft	79 lm/W

Project	
Qty	
Date	
Client	

Standard CCT



Waterproof Solution



LED Type	SMD5050RGBW
Input Voltage	24VDC
Beam Angle	120°
CRI	80+
Power	R: 4.8W/M (1.46W/ft.); G: 4.8W/M (1.46W/ft.); B: 4.8W/M (1.46W/ft.); W: 4.8W/M (1.46W/ft); RGBW 5.85W/ft
Current	R: 0.2A/m (0.061A/ft); G: 0.2A/m (0.061A/ft); B: 0.2A/m (0.061A/ft); W: 0.2A/m (0.061A/ft)
Brightness	R: 35lm/ft; G: 91lm/ft; B: 27lm/ft; W: 113lm/ft (3000K), 116lm/ft (4000K); RGBW 270lm/ft
Length/ Reel	5m(16.4ft)/ 50m/(164ft)
Cut Length	100mm/unit (3.94in/unit)
Max. Length	5m
IP Grade	IP33/ IP55/ IP65/ IP67
Operating Temperature	-20°C~45°C
Environment Humidity	40-70% RH
Dimming Method	0-10V, RX, PWM, Triac, RF, Bluetooth, WIFI etc.
Certification	CE, UL, RoHS

DIMENSION

