


JLS8120	24	8	AA	BB	80	DD
Model	Voltage	Width	CCT	IP	CRI	Length
	24: 24V	8: 8mm	27: 2700K 30: 3000K 40: 4000K 60: 6000K	33: IP33 (Dry) 55: IP55 (Wet) 65: IP65 (Wet) 67: IP67 (Wet)	80: 80+	5m (SD) 50m (MS) Customized



CCT	Power	Brightness	Luminous Flux
2700K	4.4 W/ft	447 lm/ft	102 lm/W
3000K	4.4 W/ft	480 lm/ft	109 lm/W
4000K	4.4 W/ft	509 lm/ft	116 lm/W
6000K	4.4 W/ft	496 lm/ft	113 lm/W

Project	
Qty	
Date	
Client	

## Standard CCT



LED Type	SMD2835 white
Input Voltage	24VDC
Beam Angle	120°
CRI	80+
Power	14.4W/m (4.4W/ft.)
Current	0.6A/m (0.183A/ft)
Brightness	447lm/ft (2700K); 480lm/ft(3000K); 509lm/ft (4000K); 496lm/ft (6000K)
Length/ Reel	5m(16.4ft)/ 50m(164ft)
Cut Length	50mm/unit (1.97in/unit)
Max. Length	7m
IP Grade	IP33/ IP55/ IP65/ IP67
Operating Temperature	-20°C~45°C
Environment Humidity	40-70% RH
LED CCT	3000K/ 4000K
Dimming Method	0-10V, RX, PWM, Triac, RF, Bluetooth, WIFI etc.
Certification	CE, UL, RoHS

## Waterproof Solution

<b>IP33</b> No waterproof Dry location	<b>IP55</b> Silicone Coating Wet location
<b>IP65</b> Waterproof Wet location	<b>IP67</b> Silicone Extrusion Wet location Short time under water

## DIMENSION

