CC2P

Non-peeled wire joint.



Project	
Qty	
Date	
Client	

Rated current	<10A
Rated voltage	<300V
Color	Black & Red
Contact surface	Cu
Shell material	Polycarbonate
Contact sheet	Environmental protection hardware material high precision copper
Contact sheet surface treatment	Environmental protection and anti-corrosion treatment
Working environment	-20°C~80°C
Temperature resistance	Shell -45°~135°
Flame retardant rating	UL-94-V0
Suitable wire	Stranded AWG22 ~ AWG18 (0.35 mm² ~ 0.75 mm²)
Suitable wire diameter (including insulating layer)	Φ1.5 mm ~ Φ 2.1mm
Suitable wire type	Compatible with various cables: single solid, strand, soft cable, etc.
IP Grade	IP33

INSTALLATION GUIDE

WARNING Failure to comply with the following installation instructions may result in death or serious injury.


- This product must be installed by a professional familiar with the construction and operation of the product and the hazards involved, in accordance with applicable national and local electrical and construction codes.
- To avoid electrical shock, make sure to disconnect power before install or service.
- Do not use parts that are damaged.

A CAUTION

- If received with missing or damaged parts, please contact Joyolight at 647-496-8107 (CA) or 1-877-849-1942 (US).
- · Handle with care throughout the installation in case of damages.
- · Unauthorized field repairs will void warranty.

STEP 2:


Use pliers to press the cover down tightly until you hear a "click".




STEP 1:

Lift up the red plastic covers up and insert wires into the slot, NO NEED TO PEEL THE JACKET.

Make sure to match the polarity of the wires. (+ to +; - to -)



Installation completed.



JOYOUGHt